



Fusible and Non-fusible Disconnect Switches, Accessories

Contin- uous cur- rent rating	Switch max. fused HP rating 50-60 Hz, 3-phase					Type Complete type with suffixes from columns on the right	Max. fuse clip	With fuse blocks and clips ¹⁾ for:								
	200V HP	230V HP	460V HP	575V HP	Class H fuses 250 V			Class H or J fuses 600 V	Class R fuses 250 V	600 V	Type Suffix	Price	Type Suffix	Price	Type Suffix	Price
A							A	Article No. ²⁾ see price list		Article No. ²⁾ see price list		Article No. ²⁾ see price list		Article No. ²⁾ see price list		
Fusible disconnect switches open type																
30	7½	10	20	25		P2-30/F-...	30	C13-CNA 105989		C23-CNA ³⁾ 105991		C33-CNA 105993		C36-CNA		
							60	C16-CNA 105990		C26-CNA 105992		C43-CNA 105994		C46-CNA 105995		
60	15	20	40	50		P2-60/F-...	60	C16-CNA 106001		C26-CNA 106002		C43-CNA 106004		C46-CNA 106005		
							100	C110-CNA 106000		C110-CNA 106000		C310-CNA 106003		C310-CNA 106003		
100	30	40	60	75		P2-100/F-..	100	C110-CNA 105983		C110-CNA 105983		C310-CNA 105984		C310-CNA 105984		


Continuous current	Max. HP rating 50-60 Hz, 3-phase					Type (load terminals included)	Price
A	200V HP	230V HP	460V HP	575V HP		Article No.	see price list
Non-fusible disconnect switches open type							
30	7½	10	20	25		P2-30-CNA 105987	Operating handles not included. See below. For molded case switches up to 600A, refer to Section 09.
60	15	20	40	50		P2-60-CNA 105998	
100	30	40	60	75		P2-100-CNA 105979	

Accessories

Rotary-action operating handles
for P2-... fusible and non-fusible disconnect switches

	For manual operation with door open. No cover interlock.	H6U 093191	H6U and H6-SW-NA handles are ac- cessories from the NZM molded case circuit breaker line. Refer to Section 09 for further information.
	Door-mounted with cover interlock and padlock feature. Color: black	H6-SW-NA 088865	

Auxiliary contacts

Circuit diagram	Type suffix	Price	Type	Price
	when ordered with device	see price list	when ordered separately for field installation	see price list
	+HI22-P2 105930		HI22-P2 105964	Easy bolt-on installation Visible contacts 2 N.O., 2 N.C.

Notes:

- Price includes fuse holders, but not fuses or operating handle.
- Article No. designates the complete switch, c/w fuse base and clips.
- Type C23-CNA for Class J fuses only. For Class H fuses, specify Type C38-CNA as a substitute.

Fuse Blocks
Type F ¹⁾

Ampere Rating	With fuse holders for non-time delay fuses or dual element (time delay fuses. "H" dimensions		With fuse holders for Class "J" fuses "J" dimensions to 600 V	With fuse holders for Class "R" fuses		Type	Price
	250 V	600 V		250 V	600 V		
							see price list
Fuse clip kits 6 clips per kit							
30	30	-	-	-	-	F 30-C 13-CNA 116653	
	-	30	-	-	-	F 30-C 38-CNA 166974	
	-	-	30	-	-	F 30-C 23-CNA 145633	
	-	-	-	30	-	F 30-C 33-CNA 116655	
	-	-	-	-	30	F 30-C 36-CNA 166975	
60	60	-	-	-	-	F 60/100-C 16-CNA 117477	
	-	60	60	-	-	F 60/100-C 26-CNA 114681	
	-	-	-	60	-	F 60/100-C 43-CNA 115223	
	-	-	-	-	60	F 60/100-C 46-CNA 117480	
100	100	100	100	-	-	F 60/100-C 110-CNA 117712	
	-	-	-	100	100	F 60/100-C 310-CNA 117714	

Notes:

¹⁾ fuses not included