






Thermal Overload Relays Accessories

		For use with	Type	Price	
			Article no.	See Price List	
Bases					
For separate mounting		Z00	EZ00 022630		For snap mounting on an EN 50 022 DIN rail or screw mounting
		Z1	EZ1 025003		
Pushbuttons					
For enclosed overload relays Mounting diameter 22.5 mm					
External reset button, IP65					
Front ring	Titanium color		M22-DZ-B-GB14 254834		Blue button plate: RESET
					
Stop button, IP65 (order both, the operator and the button plate)					
Front ring	Titanium color No button plate		M22-DZ-X 254835		
	Red button plate; STOP		M22-XD-R-GB0 218194		

**Thermal Overload Relays
Accessories**

	For use with	Type Article no.	Price See Price List
Shrouds			
	Z5-.../FF250	Z5/FF250-XHB 215217	Overload relay for separate mounting
			Z5/FF250-XHB
			Z5-.../FF250
	Direct mounting of Z5-.../FF250 to DILM185, DILM225, DILM250	Z5/FF250-XHB-Z 215218	Overload relay mounted directly to contactor
			DIL M400-XHB
			DIL M185/225/250
			Z5/FF250-XHB-Z
			Z5-.../FF250
			Z5/FF250-XHB
Terminals			
	Z5-FF250	Z5-FF250-XK-CNA 229314	UL recognized / CSA approved. 1 set of 3 terminals. Wire size # 6 AWG - 350 MCM

Thermal Overload Relays,
Thermistor Overload Relays