
























**RMQ Titan**  
LED Elements

	Rated operational voltage	Rated operational current	Service life at $T_a = +25\text{ }^\circ\text{C}$	Color	Type Article no.	Price See Price List
<b>LED elements with screw terminals</b>						
						
<b>Front mounting</b>						
	12 – 30 V AC/DC	8 – 15 mA 0.26W at 24V	100 000 h	○ white	M22-LED-W 216557	
				● red	M22-LED-R 216558	
				● green	M22-LED-G 216559	
				● blue	M22-LED-B 218057	
	85 – 264 V AC 50/60Hz	5 – 15 mA, $P_{max.} = 0.33\text{ W}$	100 000 h	○ white	M22-LED230-W 216563	
				● red	M22-LED230-R 216564	
				● green	M22-LED230-G 216565	
				● blue	M22-LED230-B 218059	
<b>Base mounting</b>						
	12 – 30 V AC/DC	8 – 15 mA 0.26W at 24V	100 000 h	○ white	M22-LEDC-W 216560	
				● red	M22-LEDC-R 216561	
				● green	M22-LEDC-G 216562	
				● blue	M22-LEDC-B 218058	
	85 – 264 V AC 50/60Hz	5 – 15 mA, $P_{max.} = 0.33\text{ W}$	100 000 h	○ white	M22-LEDC230-W 216566	
				● red	M22-LEDC230-R 216567	
				● green	M22-LEDC230-G 216568	
				● blue	M22-LEDC230-B 218060	
<b>LED elements with terminal screws front and base mounting</b>						
						
<b>LED Resistor Element</b> to connect 12 – 30 V LED's to:						
	42 – 60 V AC/DC				M22-XLED60 231078	
<b>LED Test Element</b> for function testing (lamp test)						
for connection to:						
	12 – 30 V AC/DC				M22-XLED-T 231079	
	85 – 264 V AC				M22-XLED230-T 231080	

Notes	Color of lens, thumb-grip	→	Color of LED
	M22(S)-L(H)-...	-R →	-R
	M22(S)-D(R)L(H)-...	-G →	-G
	M22(S)-W(R)LK-...	-W →	-W
		-Y →	-W
		-B →	-W, -B

## RMQ Titan LED Elements

	Rated operational voltage	Rated operational current	Service life at $T_a = +25\text{ }^\circ\text{C}$	Color	Type Article no.	Price See Price List
<b>LED elements with Cage Clamp<sup>1)</sup></b>						
						
<b>Front mounting</b>						
	12 – 30 V AC/DC	8 – 15 mA 0.26W at 24V	100 000 h	 white	M22-CLED-W 216569	
				 red	M22-CLED-R 216570	
				 green	M22-CLED-G 216571	
				 blue	M22-CLED-B 218061	
	85 – 264 V AC 50/60Hz	5 – 15 mA, $P_{max.} = 0.33\text{ W}$	100 000 h	 white	M22-CLED230-W 216575	
				 red	M22-CLED230-R 216576	
				 green	M22-CLED230-G 216577	
				 blue	M22-CLED230-B 218063	
<b>Base mounting</b>						
	12 – 30 V AC/DC	8 – 15 mA 0.26W at 24V	100 000 h	 white	M22-CLEDC-W 216572	
				 red	M22-CLEDC-R 216573	
				 green	M22-CLEDC-G 216574	
				 blue	M22-CLEDC-B 218062	
	85 – 264 V AC 50/60Hz	5 – 15 mA, $P_{max.} = 0.33\text{ W}$	100 000 h	 white	M22-CLEDC230-W 216578	
				 red	M22-CLEDC230-R 216579	
				 green	M22-CLEDC230-G 216580	
				 blue	M22-CLEDC230-B 218064	

**Notes**

<sup>1)</sup> Cage Clamp is a registered trademark of Wago Contact Technik GmbH, Minden, Germany

Color of lens, thumb-grip	→	Color of LED
M22(S)-L(H)-...	-R →	-R
M22(S)-D(R)L(H)-...	-G →	-G
M22(S)-W(R)LK-...	-W →	-W
	-Y →	-W
	-B →	-W, -B